

## AGRIMAX RT 955 - Especificações técnicas



### Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	300/85 R 42 (11.2 R 42)
LI/SS	144 A8/B

## Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1577
Static Loaded Radius (mm)	745
Rolling Circumference (mm)	4850
SRI (mm)	750
Rim Rec	W 9
Rim Alt	W 10 ; W 11
ECE	E4-106R-001396
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1150	1485	1795	1960	2100	2300	2495	2660	2800	-
40	1150	1485	1795	1960	2100	2300	2495	2660	2800	-
30	1230	1590	1920	2100	2250	2460	2670	2850	3000	-
10	1305	1640	2020	2395	2775	2860	3195	3530	3865	4200

Printed on 26/04/2024 08:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..