

AGRIMAX RT 955 - Especificações técnicas



Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	300/95 R 46 (12.4 R 46)
LI/SS	148 A8/B

Dimensions US Standard

Usa code	94021871
Section Width (inch)	11.6
Overall Diameter (inch)	68.4
Static Loaded Radius (inch)	32
Rolling Circumference (inch)	209.4
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E4-106R-000790
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52	58	64
30	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
25	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
20	2610	3050	3510	3950	4400	4760	5210	5590	6110	6620	7080	7440	-
10	3000	3510	4020	4530	5050	5470	5990	6420	7010	7610	8120	8540	-
5	3360	3940	4510	5090	5670	6140	6710	7200	7870	8540	9120	9590	10420

Printed on 26/04/2024 08:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..