

## AGRIMAX RT 955 - Especificações técnicas



### Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	340/85 R 46 (13.6 R 46)
LI/SS	150 A8/B

## Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1746
Static Loaded Radius (mm)	826
Rolling Circumference (mm)	5346
SRI (mm)	850
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001828
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	1445	1880	2280	2480	2650	2915	3150	3350	-
40	1445	1880	2280	2480	2650	2915	3150	3350	-
30	1545	2010	2440	2655	2835	3120	3370	3585	-
10	2065	2665	3220	3520	3770	4125	4475	4775	5025

Printed on 26/04/2024 07:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..