

AGRIMAX SPARGO - Especificações técnicas



Description

AGRIMAX SPARGO é o pneu BKT específico para aplicações de culturas em linhas, projetado para reforçar a produtividade do campo, conservando o solo no longo prazo. Graças à tecnologia VF, o pneu assegura uma capacidade de carga superior com o enchimento padrão. AGRIMAX SPARGO garante uma durabilidade excepcional, associada com uma forte estabilidade, tanto no campo como durante as deslocções na estrada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola

Version	STANDARD
Type	TL
Tyre Size	VF 380/85 R 38
LI/SS	161 D

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	730
Rolling Circumference (mm)	4830
SRI (mm)	775
Rim Rec	W 13 A
Rim Alt	W 12
ECE	E4-106R-001482
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	2480	2775	3025	3195	3320	3445	3570	3740	3910	4035	4205
From 65 to 40	2725	3050	3330	3515	3650	3790	3930	4115	4300	4440	4625
30	2780	3110	3390	3580	3720	3865	4005	4195	4380	4525	4715
20	2835	3170	3460	3655	3795	3940	4085	4280	4470	4615	4810
10	3000	3355	3660	3860	4015	4165	4320	4525	4725	4880	5085

Printed on 19/04/2024 21:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..