

AGRIMAX SPARGO - Especificações técnicas



Description

AGRIMAX SPARGO é o pneu BKT específico para aplicações de culturas em linhas, projetado para reforçar a produtividade do campo, conservando o solo no longo prazo. Graças à tecnologia VF, o pneu assegura uma capacidade de carga superior com o enchimento padrão. AGRIMAX SPARGO garante uma durabilidade excepcional, associada com uma forte estabilidade, tanto no campo como durante as deslocamentos na estrada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola

Version	STANDARD
Type	TL
Tyre Size	VF 480/95 R 50
LI/SS	181 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	2182
Static Loaded Radius (mm)	991
Rolling Circumference (mm)	6606
SRI (mm)	1025
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-0010083
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	4045	4500	5035	5495	5800	6025	6255	6485	6790	7095	7325	7630
From 65 to 40	4375	4865	5445	5940	6270	6515	6765	7015	7345	7675	7920	8250
30	4460	4960	5550	6060	6400	6645	6900	7155	7490	7825	8080	8415
20	4550	5060	5660	6180	6525	6775	7035	7295	7635	7980	8240	8580
10	4810	5350	5985	6535	6900	7165	7440	7715	8075	8440	8715	9075

Printed on 19/04/2024 21:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..