

## AGRIMAX SPARGO - Dados técnicos



### Description

AGRIMAX SPARGO é o pneu BKT específico para aplicações de culturas em linhas, projetado para reforçar a produtividade do campo, conservando o solo no longo prazo. Graças à tecnologia VF, o pneu assegura uma capacidade de carga superior com o enchimento padrão. AGRIMAX SPARGO garante uma durabilidade excepcional, associada com uma forte estabilidade, tanto no campo como durante as deslocções na estrada.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agricultura: Pulverizador agrícola

| SIZE               | Version      | USACode  | TRA Code | LI/SS | RIM REC | RIM ALT                        | SW   | OD   | SLR  | RC    | Type | ECE              |
|--------------------|--------------|----------|----------|-------|---------|--------------------------------|------|------|------|-------|------|------------------|
| VF 380/85 R 34     | STANDARD     | 94075331 | R1       | 160 D | W 13 A  | W 12                           | 15   | 59.1 | 26.7 | 177.7 | TL   | E11-106R-009071  |
| VF 380/85 R 38     | STANDARD     | 94045303 | R1       | 161 D | W 13 A  | W 12                           | 15   | 63.1 | 28.7 | 190.2 | TL   | E4-106R-001482   |
| VF 320/90 R 42     | STANDARD     | 94070978 | R1       | 163 D | W 11    | W 10 ; DW 10 ; W 10 L ; DW 11  | 12.7 | 64.6 | 30.1 | 196.7 | TL   | E11-106R-007813  |
| VF 480/80 R 42     | STANDARD     | 94075317 | R1       | 176 D | DW 16 L | DW 15 L                        | 18.9 | 72.2 | 33   | 219.4 | TL   | E11-106R-009072  |
| VF 320/90 R 46     | STANDARD     | 94075645 | R1       | 165 D | W 11    | W 10 ; DW 10 ; W 10 L ; DW 11  | 12.7 | 68.6 | 31.9 | 209.3 | TL   | E11-106R-0010077 |
| VF 380/90 R 46     | STANDARD     | 94038756 | R1       | 173 D | DW 13 B | W 13 A ; DW 12                 | 15.4 | 72.9 | 33.3 | 220.9 | TL   | E4-106R-000796   |
| VF 380/90 R 46     | STANDARD     | 94070206 | R1       | 175 D | DW 13 B | W 13 A ; DW 12                 | 15.4 | 72.9 | 33.4 | 219.8 | TL   | E11-106R-007527  |
| VF 480/80 R 46     | STANDARD     | 94057306 | R1       | 177 D | DW 16 L | DW 15 L                        | 18.9 | 76.2 | 35.1 | 232.6 | TL   | E11-106R-004756  |
| VF750/60R46        | STEEL BELTED | 94075652 | R1       | 189 D | DW27B   |                                | 29.7 | 82.1 | 37   | 249.5 | TL   | E11-106R-009075  |
| VF 320/90 R 50     | STANDARD     | 94069545 | R1       | 169 D | W 11    | W 10 ; DW 10 ; W 10 L ; DW 11  | 12.7 | 72.7 | 34.1 | 222.4 | TL   | E11-106R-007204  |
| VF 380/105 R 50    | STANDARD     | 94048113 | R1       | 179 D | W 13 A  | W 12 ; DW 12 ; DW 13 ; DW 13 L | 15.7 | 80.7 | 36.8 | 244.5 | TL   | E4-106R-002397   |
| VF 380/90 R 50     | STANDARD     | 94065264 | R1       | 175 D | W13 B   | W12 B                          | 15.4 | 76.8 | 35.2 | 234.3 | TL   | E11-106R-006400  |
| VF 420/95 R 50     | STANDARD     | 94051380 | R1       | 177 D | DW 14   | DW 13 ; W 13 ; W 14            | 16.5 | 81.4 | 37.1 | 244.5 | TL   | E4-106R-002651   |
| VF 480/80 R 50     | STANDARD     | 94057290 | R1       | 179 D | DW 16 L | DW 15 L                        | 18.9 | 80.2 | 37.3 | 245   | TL   | E11-106R-004757  |
| VF 480/95 R 50     | STANDARD     | 94075638 | R1       | 181 D | DW 16 L | DW 15 L                        | 18.9 | 85.9 | 39   | 260.1 | TL   | E11-106R-0010083 |
| VF 320/90 R 54 CFO | STANDARD     | 94075249 | R1       | 168 D | W 11    | W 10 ; DW 10 ; W 10 L ; DW 11  | 12.7 | 76.7 | 35.8 | 234.1 | TL   | E11-106R-009070  |
| VF 380/105 R 54    | STANDARD     | 94075843 | R1       | 180 D | W 13 A  | W 12 ; DW 12 ; DW 13 ; DW 13 L | 15.7 | 84.3 | 38.7 | 256   | TL   | E11-106R-0010148 |
| VF 380/90 R 54     | STANDARD     | 94075614 | R1       | 176 D | W13     | DW 13 ; DW 12 ; W 12           | 15.1 | 80.9 | 37.3 | 245.4 | TL   | E11-106R-0010081 |

Printed on 20/04/2024 00:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..