

AGRIMAX SPARGO - Dados técnicos



Description

AGRIMAX SPARGO é o pneu BKT específico para aplicações de culturas em linhas, projetado para reforçar a produtividade do campo, conservando o solo no longo prazo. Graças à tecnologia VF, o pneu assegura uma capacidade de carga superior com o enchimento padrão. AGRIMAX SPARGO garante uma durabilidade excepcional, associada com uma forte estabilidade, tanto no campo como durante as deslocamentos na estrada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
VF 380/85 R 34	STANDARD	94075331	R1	160 D	W 13 A	W 12	15	59.1	26.7	177.7	TL	E11-106R-009071
VF 380/85 R 38	STANDARD	94045303	R1	161 D	W 13 A	W 12	15	63.1	28.7	190.2	TL	E4-106R-001482
VF 320/90 R 42	STANDARD	94070978	R1	163 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	12.7	64.6	30.1	196.7	TL	E11-106R-007813
VF 480/80 R 42	STANDARD	94075317	R1	176 D	DW 16 L	DW 15 L	18.9	72.2	33	219.4	TL	E11-106R-009072
VF 320/90 R 46	STANDARD	94075645	R1	165 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	12.7	68.6	31.9	209.3	TL	E11-106R-0010077
VF 380/90 R 46	STANDARD	94070206	R1	175 D	DW 13 A	W 13 A ; DW 12	15.4	72.9	33.4	219.8	TL	E11-106R-007527
VF 380/90 R 46	STANDARD	94038756	R1	173 D	DW 13 A	W 13 A ; DW 12	15.4	72.9	33.3	220.9	TL	E4-106R-000796
VF 480/80 R 46	STANDARD	94057306	R1	177 D	DW 16 L	DW 15 L	18.9	76.2	35.1	232.6	TL	E11-106R-004756
VF750/60R46	STEEL BELTED	94075652	R1	189 D	DW27B		29.7	82.1	37	249.5	TL	E11-106R-009075
VF 320/90 R 50	STANDARD	94069545	R1	169 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	12.7	72.7	34.1	222.4	TL	E11-106R-007204
VF 380/105 R 50	STANDARD	94048113	R1	179 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	15.7	80.7	36.8	244.5	TL	E4-106R-002397
VF 380/90 R 50	STANDARD	94065264	R1	175 D	W13 B	W12 B	15.4	76.8	35.2	234.3	TL	E11-106R-006400
VF 420/95 R 50	STANDARD	94051380	R1	177 D	DW 14	DW 13 ; W 13 ; W 14	16.5	81.4	37.1	244.5	TL	E4-106R-002651
VF 480/80 R 50	STANDARD	94057290	R1	179 D	DW 16 L	DW 15 L	18.9	80.2	37.3	245	TL	E11-106R-004757
VF 480/95 R 50	STANDARD	94075638	R1	181 D	DW 16 L	DW 15 L	18.9	85.9	39	260.1	TL	E11-106R-0010083
VF 320/90 R 54 CFO	STANDARD	94075249	R1	168 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	12.7	76.7	35.8	234.1	TL	E11-106R-009070
VF 380/105 R 54	STANDARD	94075843	R1	180 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	15.7	84.3	38.7	256	TL	E11-106R-0010148
VF 380/90 R 54	STANDARD	94075614	R1	176 D	W13	DW 13 ; DW 12 ; W 12	15.1	80.9	37.3	245.4	TL	E11-106R-0010081

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/03/2025 10:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..