

## AIROMAX AM 27 - Especificações técnicas



### Description

AIROMAX AM 27 é um pneu para ser utilizado principalmente na estrada, ideal para as aplicações com guindaste no setor das construções. O pneu destaca-se pela resistência ao calor e pelo conforto excepcional. AIROMAX AM 27 é um pneu de alta velocidade, apropriado particularmente para todas as operações que exigem um nível elevado de capacidade de manobra.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Guindaste móvel

Version	STANDARD
Type	TL
Tyre Size	505/95 R 25 (18.00 R 25)
LI/SS	186 E

## Dimensions International Standard

Overall Width (mm)	492
Overall Diameter (mm)	1600
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4900
Rim Rec	13.00/2.5

## Load capacity (Kg)

km/h / bar	9.00
30	12350
40	11800
50	11200
60	10650
70	9500
80	7800
90	6650
100	5700

Printed on 22/02/2024 20:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..