

AIROMAX AM 27 - Especificações técnicas



Description

AIROMAX AM 27 é um pneu para ser utilizado principalmente na estrada, ideal para as aplicações com guindaste no setor das construções. O pneu destaca-se pela resistência ao calor e pelo conforto excepcional. AIROMAX AM 27 é um pneu de alta velocidade, apropriado particularmente para todas as operações que exigem um nível elevado de capacidade de manobra.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Guindaste móvel

Version	STANDARD
Type	TL
Tyre Size	505/95 R 25 (18.00 R 25)
LI/SS	186 E

Dimensions US Standard

Usa code	94045198
Overall Width (inch)	19.4
Overall Diameter (inch)	63
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	192.9
Rim Rec	13.00/2.5

Load capacity (lbs)

mph / psi	130
20	27200
25	26000
30	24700
35	23500
43	20900
50	17200
55	14700
62	12600

Printed on 26/04/2024 10:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..