

AIROMAX AM 543 - Especificações técnicas



Description

AIROMAX AM 543 é o pneu ideal para aplicações com guindaste no setor das construções. O pneu apresenta uma tração excelente com uma estabilidade elevada. Dado que os pneus para guindastes são sujeitos a condições de emprego extremas, AIROMAX AM 543 foi projetado para proporcionar uma ótima resistência ao calor. Além disso, é apropriado para todas as operações em que é exigido um nível elevado de capacidade de manobra.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Guindaste móvel

Version	STANDARD
Type	TT
Tyre Size	385/95 R 24 (14.00 R 24)
LI/SS	170 E

Dimensions US Standard

Usa code	94064502
Overall Width (inch)	14.8
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	163.6
Rim Rec	10.00W

Load capacity (lbs)

mph / psi	130
43	13200

Printed on 19/04/2024 17:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..