

AS 2001 - Especificações técnicas



Description

AS 2001 é um pneu diagonal de lonas cruzadas, muito apropriado para tratores nas operações de trabalho de terreno e de transporte. O desenho assegura uma tração excelente e ótimas propriedades de autolimpagem. AS 2001 é realizado com um composto de borracha resistente a todos os tipos de corte, que fornece uma elevada capacidade de carga.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94002825
Ply Rating	12
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	170
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004345
TRA Code	R1

Load capacity (lbs)

	mph / psi	36
	25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 08:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..