

AS 2001 - Especificações técnicas



Description

AS 2001 é um pneu diagonal de lonas cruzadas, muito apropriado para tratores nas operações de trabalho de terreno e de transporte. O desenho assegura uma tração excelente e ótimas propriedades de autolimpagem. AS 2001 é realizado com um composto de borracha resistente a todos os tipos de corte, que fornece uma elevada capacidade de carga.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	18.4 - 26
LI/SS	142 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	467
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	650
Rolling Circumference (mm)	4250
SRI (mm)	675
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003367
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.80
30	2650

Printed on 25/04/2024 06:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..