AS 504 - Especificações técnicas

Description

AS 504 é um pneu agroindustrial especialmente desenvolvido para aplicações de trabalhos da terra e operações de mani manipulação de material. Este pneu, que se destaca pelas propriedades excelentes de autolimpagem e pela adesão potenciada, é ideal para reboques e levantadores telescópicos. Estão disponíveis diferentes versões de pneu AS 504 para satisfazer as exigências específicas do utilizador: uma versão “HD” com um composto resistente aos cortes e às lacerações, enquanto a versão “special” é dotada de uma carcaça reforçada que assegura um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

BIAS

Machinery

Agricultura: Levantador telescópico • Reboque para os campos
Industrial: Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions US Standard

Usa code	94018703
Ply Rating	10
Section Width (inch)	11.4
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100
Rim Rec	9.00

Load capacity (lbs)

mph / psi	49
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 26/04/2024 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..