AS 504 - Especificações técnicas

Description

AS 504 é um pneu agroindustrial especialmente desenvolvido para aplicações de trabalhos da terra e operações de mani manipulação de material. Este pneu, que se destaca pelas propriedades excelentes de autolimpagem e pela adesão potenciada, é ideal para reboques e levantadores telescópicos. Estão disponíveis diferentes versões de pneu AS 504 para satisfazer as exigências específicas do utilizador: uma versão "HD" com um composto resistente aos cortes e às lacerações, enquanto a versão "special" é dotada de uma carcaça reforçada que assegura um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Levantador telescópico • Reboque para os campos
Industrial: Levantador telescópico

Version	STANDARD
Type	TT
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	290
Overall Diameter (mm)	867
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2540
SRI (mm)	410
Rim Rec	9.00
ECE	E11-106R-003510

Load capacity (Kg)

km/h / bar	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Printed on 25/04/2024 03:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..