AS 504 - Especificações técnicas

Description

AS 504 é um pneu agroindustrial especialmente desenvolvido para aplicações de trabalhos da terra e operações de mani manipulação de material. Este pneu, que se destaca pelas propriedades excelentes de autolimpagem e pela adesão potenciada, é ideal para reboques e levantadores telescópicos. Estão disponíveis diferentes versões de pneu AS 504 para satisfazer as exigências específicas do utilizador: uma versão “HD” com um composto resistente aos cortes e às lacerações, enquanto a versão “special” é dotada de uma carcaça reforçada que assegura um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

BIAS

Machinery

Agricultura: Levantador telescópico • Reboque para os campos
Industrial: Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS DRIVE WHEEL	139 A8
LI/SS FREE ROLLING	151 A8

Dimensions US Standard

Usa code	94019045
Ply Rating	12
Section Width (inch)	16.5
Overall Diameter (inch)	43.2
Static Loaded Radius (inch)	19.2
Rolling Circumference (inch)	126.5
Rim Rec	13
Rim Alt	12 SDC ; 14 ; 13 SDC
ECE	E11-106R-004610

Load capacity (lbs)

mph / psi	44
5 FR	10650
15 FR	9050
20 FR	8520
25 FR	7610
5 DW	7500
15 DW	6370
20 DW	6000
25 DW	5360

Printed on 20/04/2024 02:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..