

AS 509 - Especificações técnicas



Description

AS 509 foi especialmente desenvolvido para reboques, compressores de palha e implementos agrícolas. O pneu garantem uma elevada capacidade de carga de baixas pressões, protegendo as culturas. AS 509 assegura maior tração e ótimas propriedades de autolimpagem.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/45 - 22.5 |
| LI/SS DRIVE WHEEL | 141 A8/137 B |
| LI/SS FREE ROLLING | 153 A8/149 B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 540 |
| Overall Diameter (mm) | 1065 |
| Static Loaded Radius (mm) | 479 |
| Rolling Circumference (mm) | 3250 |
| Rim Rec | AG 16.00 |
| ECE | E11-106R-006445 |

Load capacity (Kg)

| km/h / bar | 1.50 | 1.80 | 2.10 |
|------------|------|------|------|
| 10 FR | 4200 | 4670 | 5110 |
| 20 FR | 3780 | 4200 | 4600 |
| 30 FR | 3360 | 3735 | 4090 |
| 40 FR | 3000 | 3335 | 3650 |
| 50 FR | 2700 | 3000 | 3250 |
| 10 DW | 2960 | 3295 | 3605 |
| 20 DW | 2665 | 2965 | 3245 |
| 30 DW | 2370 | 2640 | 2885 |
| 40 DW | 2115 | 2355 | 2575 |
| 50 DW | 1905 | 2120 | 2300 |

Printed on 20/04/2024 15:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..