

AS 511 - Especificações técnicas



Description

AS 511 é muito apropriado para implementos agrícolas nas aplicações com prados. A carcaça robusta e o composto de borracha especialmente resistente aos cortes oferecem uma estabilidade elevada e um melhor desempenho. Graças a uma ampla área de contacto, AS 511 assegura uma tração excelente e minimiza a compactação do solo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Implementos agrícolas

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 R 15
LI/SS	122 B

Dimensions International Standard

Section Width (mm)	388
Overall Diameter (mm)	785
Static Loaded Radius (mm)	353
Rolling Circumference (mm)	2387
SRI (mm)	380
Rim Rec	13 LB
ECE	E11-106R-005098

Load capacity (Kg)

km/h / bar	2.8
50	1500

Printed on 26/04/2024 19:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..