

## AT 111 HD - Especificações técnicas



### Description

AT 111 HD é apropriado para aplicações desportivas de corrida todo-o-terreno com veículos ATV. A profundidade aumentada do piso do pneu e a forte espessura dos flancos proporcionam uma imensa aderência e controlo de travagem, associados com uma tração excelente e controlo com alta velocidade nas manobras com excesso de direção. AT 111 HD assegura um ciclo de vida longo do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Veículo ATV

|           |                |
|-----------|----------------|
| Version   | STANDARD       |
| Type      | TL             |
| Tyre Size | AT 22 X 11 - 9 |

## Dimensions International Standard

|                       |                |
|-----------------------|----------------|
| Ply Rating            | 6              |
| Section Width (mm)    | 279            |
| Overall Diameter (mm) | 560            |
| Rim Rec               | 9.0 AT         |
| Rim Alt               | 8.5 AT         |
| ECE                   | E4-75R-0006332 |

## Load capacity (Kg)

| km/h / bar | 0.45 |
|------------|------|
| 100        | 180  |

Printed on 20/04/2024 06:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..