

AT 171 - Especificações técnicas



Description

AT 171 foi especialmente projetado para tratores de corrida na lama. O especial desenho direcional e extra profundo do piso do pneu assegura uma tração excelente em superfícies molhadas e lamacentas.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Veículo ATV • Veículo para las corridas de lama

Version	STANDARD
Type	TL
Tyre Size	AT 30 X 9 - 14
LI/SS	77 A8 / 53 F

Dimensions International Standard

Ply Rating	6
Section Width (mm)	211
Overall Diameter (mm)	755
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (Kg)

	km/h / bar	1.40	1.00
40 MUD BOGGING		412	-
80 MUD BOGGING		206	-
40 CASUAL TRANSPORT		-	335
80 CASUAL TRANSPORT		-	170

Printed on 25/04/2024 09:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..