

AT 171 - Especificações técnicas



Description

AT 171 foi especialmente projetado para tratores de corrida na lama. O especial desenho direcional e extra profundo do piso do pneu assegura uma tração excelente em superfícies molhadas e lamacentas.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Veículo ATV • Veículo para las corridas de lama

Version	STANDARD
Type	TT
Tyre Size	AT 35 X 9 - 20
LI/SS	85 A8 / 61 F

Dimensions International Standard

Ply Rating	6
Section Width (mm)	200
Overall Diameter (mm)	895
Static Loaded Radius (mm)	419
Rolling Circumference (mm)	2670
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (Kg)

	km/h / bar	1.40	1.00
40 MUD BOGGING		515	-
80 MUD BOGGING		257	-
40 CASUAL TRANSPORT		-	425
80 CASUAL TRANSPORT		-	218

Printed on 19/04/2024 19:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..