

## AT 171 - Especificações técnicas



### Description

AT 171 foi especialmente projetado para tratores de corrida na lama. O especial desenho direcional e extra profundo do piso do pneu assegura uma tração excelente em superfícies molhadas e lamacentas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Veículo ATV • Veículo para las corridas de lama

Version	STANDARD
Type	TL
Tyre Size	AT 40 X 9 - 24
LI/SS	90 A8 / 66 F

## Dimensions US Standard

Usa code	94056859
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	39.2
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	122.5
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

## Load capacity (lbs)

	mph / psi	20	15
25 MUD BOGGING		1323	-
50 MUD BOGGING		662	-
25 CASUAL TRANSPORT		-	1070
50 CASUL TRANSPORT		-	535

Printed on 13/04/2024 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..