

## AT 316 - Dados técnicos



### Description

AT 316 é apropriado para tratores comerciais compactos nas obras municipais e na manutenção. O desenho especial do piso do pneu assegura uma tração excelente sem comprometer a proteção do campo – uma característica essencial para este tipo de aplicação. O pneu AT 316 também está disponível em versão “aramid belted”, com cintos em aramida, que fornece uma maior resistência à perfuração.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator compacto

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 12.00 - 12	ARAMID BELTED	94001217	6	10.50   - 55 ;   - 70 ;   - 90		12.4	24	10.7	69.6	TL	
24 X 12.00 - 12	STANDARD	94001200	4	10.50   - 55 ;   - 70 ;   - 90		12.4	24	10.7	69.6	TL	E11-106R-004082

Printed on 24/04/2024 05:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..