

## AT 603 - Especificações técnicas



### Description

AT 603 é um pneu agroindustrial para implementos agrícolas e retroescavadoras. AT 603 foi projetado para assegurar uma durabilidade e tração excelente sobre roda motriz e, portanto, uma ótima performance em todas as superfícies, bem como tração excelente. AT 603 está disponível em versão "special" com carcaça reforçada, enquanto a versão "HD" proporciona uma maior resistência aos cortes e às lacerações.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Retroescavadora • Implementos agrícolas  
Industrial: Retroescavadora

Version	HD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	274
Overall Diameter (mm)	907
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2727
SRI (mm)	425
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E11-106R-004546

## Load capacity (Kg)

	km/h / bar	3.70
	10 FR	2730
	25 FR	2320
	30 FR	2185
	40 FR	1950
	10 DW	1905
	25 DW	1620
	30 DW	1525
	40 DW	1360

Printed on 26/04/2024 11:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..