

## AT 603 - Especificações técnicas



### Description

AT 603 é um pneu agroindustrial para implementos agrícolas e retroescavadoras. AT 603 foi projetado para assegurar uma durabilidade e tração excelente sobre roda motriz e, portanto, uma ótima performance em todas as superfícies, bem como tração excelente. AT 603 está disponível em versão "special" com carcaça reforçada, enquanto a versão "HD" proporciona uma maior resistência aos cortes e às lacerações.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Retroescavadora • Implementos agrícolas  
Industrial: Retroescavadora

Version	SPECIAL
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions US Standard

Usa code	94019670
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	107.4
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E11-106R-004546

## Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 26/04/2024 12:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..