

AT 603 - Especificações técnicas



Description

AT 603 é um pneu agroindustrial para implementos agrícolas e retroescavadoras. AT 603 foi projetado para assegurar uma durabilidade e tração excelente sobre roda motriz e, portanto, uma ótima performance em todas as superfícies, bem como tração excelente. AT 603 está disponível em versão "special" com carcaça reforçada, enquanto a versão "HD" proporciona uma maior resistência aos cortes e às lacerações.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Retroescavadora • Implementos agrícolas
Industrial: Retroescavadora

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions US Standard

Usa code	94019595
Ply Rating	12
Section Width (inch)	12.1
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	119.2
Rim Rec	W 9
Rim Alt	11

Load capacity (lbs)

mph / psi	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Printed on 26/04/2024 04:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..