

AT 603 - Especificações técnicas



Description

AT 603 é um pneu agroindustrial para implementos agrícolas e retroescavadoras. AT 603 foi projetado para assegurar uma durabilidade e tração excelente sobre roda motriz e, portanto, uma ótima performance em todas as superfícies, bem como tração excelente. AT 603 está disponível em versão "special" com carcaça reforçada, enquanto a versão "HD" proporciona uma maior resistência aos cortes e às lacerações.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Retroescavadora • Implementos agrícolas
Industrial: Retroescavadora

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	138 A8
LI/SS FREE ROLLING	150 A8

Dimensions US Standard

Usa code	94031269
Ply Rating	18
Section Width (inch)	12.1
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	119.2
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-004352

Load capacity (lbs)

mph / psi	80
5 FR	10340
15 FR	8780
20 FR	8270
25 FR	7390
5 DW	7290
15 DW	6190
20 DW	5830
25 DW	5200

Printed on 26/04/2024 07:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..