

## AT 603 - Especificações técnicas



### Description

AT 603 é um pneu agroindustrial para implementos agrícolas e retroescavadoras. AT 603 foi projetado para assegurar uma durabilidade e tração excelente sobre roda motriz e, portanto, uma ótima performance em todas as superfícies, bem como tração excelente. AT 603 está disponível em versão "special" com carcaça reforçada, enquanto a versão "HD" proporciona uma maior resistência aos cortes e às lacerações.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Retroescavadora • Implementos agrícolas  
Industrial: Retroescavadora

Version	STANDARD
Type	TL
Tyre Size	15.5 - 25

## Dimensions US Standard

Usa code	94059775
Ply Rating	12
Section Width (inch)	16.1
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	152
Rim Rec	12.00/1.3
Rim Alt	12.00/1.3 (DC)
TRA Code	E2/G2/L2

## Load capacity (lbs)

mph / psi	36	58	36
30	7160	-	-
5	-	12350	-
25	-	-	5840

Printed on 26/04/2024 10:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..