

AT 625 - Especificações técnicas



Description

AT 625 é apropriado para retroescavadoras e carregadoras compactas em todas as operações de escavação e carga no âmbito agrícola. O piso do pneu, super profundo, garante uma resistência acrescida à perfuração e uma maior durabilidade. AT 625 proporciona tração e estabilidade excelentes, bem como uma melhor resistência a cortes e rasgões.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Retroescavadora • Carregadora compacta

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

Dimensions US Standard

Usa code	94055470
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.4
Rolling Circumference (inch)	167.5
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (lbs)

mph / psi	38
25	7850

Printed on 20/04/2024 13:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..