

AW 09 - Especificações técnicas



Description

AW 09 foi desenvolvido para o cultivo do solo, a colheita de feno y para aplicações no transporte com implementos agrícolas, enfardadeiras de feno e reboques. É apropriado para ser utilizado na agricultura moderna, tanto na estrada como fora da estrada. A carcaça reforçada garante uma capacidade de carga elevada e uma vida operacional mais longa.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	138 A8

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	860
Static Loaded Radius (mm)	376
Rolling Circumference (mm)	2520
Rim Rec	9.00
ECE	E4-106R-000377

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	3305
	25 FR	2810
	30 FR	2645
	40 FR	2360
	10 DW	2380
	25 DW	2025
	30 DW	1905
	40 DW	1700

Printed on 24/04/2024 12:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..