AW 09 - Especificações técnicas

Description

AW 09 foi desenvolvido para o cultivo do solo, a colheita de feno y para aplicações no transporte com implementos agrícolas, enfardadeiras de feno e reboques. É apropriado para ser utilizado na agricultura moderna, tanto na estrada como fora da estrada. A carcaça reforçada garante uma capacidade de carga elevada e uma vida operacional mais longa.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	128 A8
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2491
Rim Rec	13.00
ECE	E4-106R-000380

Load capacity (Kg)

km/h / bar	3.20
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575
10 DW	2520
25 DW	2140
30 DW	2015
40 DW	1800

Printed on 20/04/2024 03:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..