AW 702 - Especificações técnicas

Description

AW 702 foi desenvolvido para implementos agrícolas, reboques e compressores de palha nas aplicações para trabalhar a terra e para o transporte. Este pneu para operações pesadas foi projetado pela BKT para proporcionar um novo nível de duração. AW 702 está disponível em versões diferentes para responder às exigências específicas dos utilizadores: uma versão “aramid belted” com cintos em aramida, que fornece uma maior resistência ás perfurações, uma versão “HD” com um composto resistente aos cortes e lacerações, enquanto a versão “special” fornece una resistência aos restolhos.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas • Reboque
Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	130 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	274
Overall Diameter (mm)	760
Static Loaded Radius (mm)	351
Rolling Circumference (mm)	2213
Rim Rec	9.00
ECE	E4-106R-001896

Load capacity (Kg)

km/h / bar	5.50
10 FR	2660
25 FR	2260
30 FR	2130
40 FR	1900

Printed on 09/05/2024 22:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..