

AW 705 - Especificações técnicas



Description

AW 705 foi desenvolvido para implementos agrícolas, reboques y compressores de palha nas aplicações para trabalhar a terra e para o transporte. É apropriado para ser utilizado na agricultura moderna graças a uma durabilidade superior e uma capacidade de carga elevada.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 14.0/65 - 16 |
| LI/SS FREE ROLLING | 134 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94009916 |
| Ply Rating | 10 |
| Section Width (inch) | 13.9 |
| Overall Diameter (inch) | 34.3 |
| Static Loaded Radius (inch) | 15.3 |
| Rolling Circumference (inch) | 100.4 |
| Rim Rec | 11.0 |

Load capacity (lbs)

| mph / psi | 41 |
|-----------|------|
| 5 FR | 6550 |
| 15 FR | 5570 |
| 20 FR | 5240 |
| 25 FR | 4670 |

Printed on 20/04/2024 08:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..