

AW 705 - Especificações técnicas



Description

AW 705 foi desenvolvido para implementos agrícolas, reboques y compressores de palha nas aplicações para trabalhar a terra e para o transporte. É apropriado para ser utilizado na agricultura moderna graças a uma durabilidade superior e uma capacidade de carga elevada.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

Version	STANDARD
Type	TL
Tyre Size	15.0/70 - 18
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	405
Overall Diameter (mm)	1010
Static Loaded Radius (mm)	447
Rolling Circumference (mm)	3092
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001902

Load capacity (Kg)

km/h / bar	3.10
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900

Printed on 20/04/2024 13:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..