

AW 708 - Especificações técnicas



Description

AW 708 foi desenvolvido para trabalhar na terra, bem como nas aplicações de transporte e recolha da palha com implementos agrícolas, reboques e prensas de palha. O pneu é disponível em uma versão "HD" com um composto resistente aos cortes e lacerações.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	138 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	470
Overall Diameter (mm)	866
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2536
Rim Rec	16.00
ECE	E4-106R-002334

Load capacity (Kg)

km/h / bar	2.25
10 FR	3305
25 FR	2810
30 FR	2645
40 FR	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 16:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..