

## AW 708 - Especificações técnicas



### Description

AW 708 foi desenvolvido para trabalhar na terra, bem como nas aplicações de transporte e recolha da palha com implementos agrícolas, reboques e prensas de palha. O pneu é disponível em uma versão "HD" com um composto resistente aos cortes e lacerações.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas  
• Reboque  
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	148 A8

## Dimensions US Standard

Usa code	94010257
Ply Rating	18
Section Width (inch)	18.5
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	99.8
Rim Rec	16.00
ECE	E4-106R-002268

## Load capacity (lbs)

mph / psi	48
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940

Printed on 19/04/2024 17:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..