

## AW 708 - Especificações técnicas



### Description

AW 708 foi desenvolvido para trabalhar na terra, bem como nas aplicações de transporte e recolha da palha com implementos agrícolas, reboques e prensas de palha. O pneu é disponível em uma versão "HD" com um composto resistente aos cortes e lacerações.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas  
• Reboque  
Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	145 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-002712

## Load capacity (Kg)

	km/h / bar	3.60
	10 FR	4060
	25 FR	3450
	30 FR	3250
	40 FR	2900

Printed on 19/04/2024 22:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..