

AW 711 - Especificações técnicas



Description

AW 711 é um pneu radial para implementos agrícolas, especificadamente projetado para ser utilizado na agricultura moderna e apropriado para aplicações de transporte, de recolha da palha e para o trabalho de terreno. Graças ao especial composto do piso, AW 711 assegura um longo ciclo de vida do produto, tanto se utilizado em superfícies macias como em superfícies duras. A baixa resistência ao rolamento durante a deslocação em estrada garante uma poupança significativa no consumo de combustível. Graças à tecnologia VF, AW 711 fornece uma capacidade de carga elevada com pressões baixas.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Implementos agrícolas

| | |
|-----------|-------------------|
| Version | STUBBLE RESISTANT |
| Type | TL |
| Tyre Size | 400/60 R 18 |
| LI/SS | 159 A8/B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 394 |
| Overall Diameter (mm) | 945 |
| Static Loaded Radius (mm) | 419 |
| Rolling Circumference (mm) | 2807 |
| SRI (mm) | 450 |
| Rim Rec | 14 |
| Rim Alt | 13 |
| ECE | E4-106R-001397 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 3.8 | 4.0 | 5.0 | 5.5 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1220 | 1585 | 1950 | 2235 | 2600 | 2965 | 3165 | 3490 | 3655 | 3815 | 4057 | 4375 |
| 40 | 1220 | 1585 | 1950 | 2235 | 2600 | 2965 | 3165 | 3490 | 3655 | 3815 | 4057 | 4375 |
| 30 | 1365 | 1775 | 2185 | 2500 | 2910 | 3320 | 3550 | 3910 | 4095 | 4275 | 4545 | 4900 |
| 25 | 1450 | 1885 | 2320 | 2660 | 3095 | 3530 | 3770 | 4155 | 4350 | 4545 | 4830 | 5210 |
| 20 | 1535 | 1995 | 2460 | 2815 | 3275 | 3735 | 3990 | 4400 | 4605 | 4810 | 5115 | 5515 |
| 10 | 1705 | 2220 | 2730 | 3125 | 3640 | 4150 | 4435 | 4885 | 5115 | 5340 | 5680 | 6125 |

Printed on 10/12/2023 12:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..