

AW 712 - Especificações técnicas



Description

AW 712 é um pneu radial para implementos agrícolas especialmente apropriado para reboques e cisternas móveis de chorume. O pneu destaca-se pela carcaça robusta e pelo composto de borracha especialmente resistente aos restos, que garantem uma durabilidade excelente. AW 712 assegura uma comodidade de condução extraordinária.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Implementos agrícolas • Pulverizador agrícola

Version	IMPLEMENT
Type	TL
Tyre Size	260/70 R 15.3
LI/SS	134 A8/B

Dimensions International Standard

Section Width (mm)	264
Overall Diameter (mm)	760
Static Loaded Radius (mm)	344
Rolling Circumference (mm)	2304
SRI (mm)	370
Rim Rec	9.00
ECE	'E11-106R-005096

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
50	615	785	955	1105	1275	1445	1550	1720	1780	1995	2120
40	615	785	955	1105	1275	1445	1550	1720	1780	1995	2120
30	690	880	1070	1235	1425	1615	1735	1925	1990	2235	2375
25	735	935	1140	1315	1515	1720	1845	2050	2115	2375	2525
20	780	990	1205	1375	1605	1820	1955	2170	2240	2515	2675
10	865	1100	1340	1545	1785	2020	2170	2410	2490	2795	2970

Printed on 23/04/2024 16:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..