

## AW 726 - Especificações técnicas



### Description

AW 726 foi especialmente desenvolvido para reboques nas aplicações de transporte. O pneu é apropriado para ser utilizado tanto na estrada como fora da estrada. AW 726 assegura desempenhos na estrada, comodidade de condução e autolimpagem excelentes. El desenho por blocos fornece um ciclo de vida prolongado do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	400
Overall Diameter (mm)	875
Rim Rec	AG 13.00
ECE	E11-106R-005341

## Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Printed on 27/04/2024 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..