

AW 726 - Dados técnicos



Description

AW 726 foi especialmente desenvolvido para reboques nas aplicações de transporte. O pneu é apropriado para ser utilizado tanto na estrada como fora da estrada. AW 726 assegura desempenhos na estrada, comodidade de condução e autolimpagem excelentes. El desenho por blocos fornece um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11.5/80 - 15.3	ARAMID BELTED	94064366	126 A8	139 A8	14	9.00		11.8	33.7	14.3	99.6	TL	E11-106R-0010913
11.5/80 - 15.3	STANDARD	94053698	126 A8	139 A8	14	9.00		11.8	33.7	14.3	99.6	TL	E11-106R-005264
11.5/80 - 15.3	STEEL BELTED	94067695	126 A8	139 A8	14	9.00		11.8	33.7	14.7	100	TL	E11-106R-006974
400/60 - 15.5	STANDARD	94054008	137 A8	149 A8	18	AG 13.00		15.7	34.4	0	0	TL	E11-106R-005341
420/55 - 17	STANDARD	94055647	121 A8	133 A8		13.00		16.3	35	15.4	101.7	TL	E11-106R-005265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/02/2025 15:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..