

AW 909 - Especificações técnicas



Description

AW 909 foi desenvolvido para trabalhar na terra, bem como para aplicações de recolha e de transporte com implementos agrícolas, reboques e compressores de palha. O pneu é apropriado para ser utilizado na agricultura moderna, tanto na estrada como fora da estrada.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	123 A8

Dimensions US Standard

Usa code	94010394
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	29.9
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.7
Rim Rec	9.00
ECE	E4-106R-001540

Load capacity (lbs)

mph / psi	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420

Printed on 26/04/2024 23:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..