

AW 909 - Especificações técnicas



Description

AW 909 foi desenvolvido para trabalhar na terra, bem como para aplicações de recolha e de transporte com implementos agrícolas, reboques e compressores de palha. O pneu é apropriado para ser utilizado na agricultura moderna, tanto na estrada como fora da estrada.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	274
Overall Diameter (mm)	760
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2227
Rim Rec	9.00
ECE	E4-106R-001541

Load capacity (Kg)

	km/h / bar	4.70
	10 FR	2380
	25 FR	2025
	30 FR	1905
	40 FR	1700

Printed on 26/04/2024 23:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..