

BK 308 - Especificações técnicas



Description

BK 308 foi especialmente projetado para reboques e tratores compactos. O pneu destaca-se pela tração excelente em todas as superfícies e elementos intermédios (tie bar) entre as barras do piso, para reduzir o efeito de fendas de esforço no piso. A carcaça robusta, realizada com um composto de borracha especial do piso, proporciona uma durabilidade excelente e uma ótima resistência contra os furos, para assegurar uma vida operacional mais ampla.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator compacto • Reboque

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	112 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	190
Overall Diameter (mm)	865
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003563

Load capacity (Kg)

km/h / bar	4.8
30	1120

Printed on 23/04/2024 18:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..