

BK 627 - Especificações técnicas



Description

BK 627 é um pneu com desenho do piso por blocos, apropriado para operações de transporte e trabalho da terra com reboques e implementos agrícolas. É destinado principalmente para ser utilizado no campo e ideal para as operações pesadas.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Trator • Reboque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	121 A8

Dimensions US Standard

Usa code	94041183
Ply Rating	12
Section Width (inch)	8.7
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	98.2
Rim Rec	6.0
ECE	E11-106R-004256

Load capacity (lbs)

mph / psi	74
25	3200

Printed on 27/04/2024 07:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..