

## BK 823 - Especificações técnicas



### Description

BK 823 é um pneu principalmente projetado para tratores, implementos agrícolas e reboques nas aplicações de transporte na estrada e no campo e de cultivo do solo. O desenho especial do piso caracterizado por blocos, torna-o especialmente apropriado para utilizações pesadas, onde uma ótima viragem representa um requisito essencial. É também disponível uma versão "HD" que proporciona uma resistência aos cortes e furos.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Trator • Reboque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	124 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	245
Overall Diameter (mm)	891
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2583
Rim Rec	6.5
ECE	E11-106R-003603

## Load capacity (Kg)

km/h / bar	3.80
40	1600

Printed on 23/04/2024 17:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..