

COMMANDER 3 RIB - Especificações técnicas



Description

COMMANDER 3 RIB é um pneu dianteiro com nervura do piso do pneu de 3 costelas idóneo para operações de trabalho de terreno e de transporte. Assegura uma durabilidade excelente e uma ótima capacidade de carga, graças à distribuição da carga otimizada nas costelas na parte central e na área do ombro. A carcaça robusta e o composto de borracha resistente aos restolhos asseguram uma resistência extraordinária aos furos.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator 2WD

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	91 A8

Dimensions US Standard

Usa code	94046911
Ply Rating	8
Section Width (inch)	6.9
Overall Diameter (inch)	29.1
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004415
TRA Code	F2

Load capacity (lbs)

mph / psi	68
25	1360

Printed on 23/04/2024 09:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..