

## COMMANDER (F) - Especificações técnicas



### Description

COMMANDER (F) é um pneu com nervura do piso de 3 rasgos - perfeito para operações de trabalho de terreno e de transporte. O piso do pneu profundo é realizado com um composto de borracha especialmente resistente a todo o tipo de corte para uma longa vida do pneu e para uma elevada capacidade de carga.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator 2WD

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	86 A6

## Dimensions International Standard

<b>Ply Rating</b>	6
<b>TKPH</b>	1
<b>Section Width (mm)</b>	155
<b>Overall Diameter (mm)</b>	720
<b>Static Loaded Radius (mm)</b>	340
<b>Rolling Circumference (mm)</b>	2145
<b>Rim Rec</b>	4.00 E
<b>Rim Alt</b>	3.50D ; 4.50E
<b>ECE</b>	E11-106R-003308
<b>TRA Code</b>	F2

## Load capacity (Kg)

km/h / bar	3.70
30	530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/03/2025 13:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..