COMMANDER (R) - Especificações técnicas

Description

COMMANDER (R) é um pneu agrícola caraterizado por um piso do pneu profundo com uma base forte dos blocos que asseguram um ciclo de vida prolongado do pneu. O desenho especial dos blocos de duplo ângulo garante tanto uma excelente tração no campo como ótimas propriedades de autolimpagem. A carcaça robusta é realizada com um composto de borracha especialmente resistente a qualquer tipo de corte, que fornece uma melhor resistência aos furos e uma elevada capacidade de carga. COMMANDER (R) é o pneu perfeito para operações de trabalho de terreno e de recolha.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Ceifeira • Trator

Version	STANDARD
Type	TT
Tyre Size	11.2 - 24
LI/SS	123 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	295
Overall Diameter (mm)	1125
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3483
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004616
TRA Code	R1

Load capacity (Kg)

km/h / bar	3.6
30	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 05:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..