

COMMANDER TWIN RIB - Especificações técnicas



Description

COMMANDER TWIN RIB é um pneu com nervura do piso de 4 rasgos e lamelas laterais nos ombros que assegura uma ótima aderência. O perfil mais largo assegura uma ótima distribuição da carga. A Carcaça robusta e o composto de borracha superior garantem um ciclo de vida prolongado. COMMANDER TWIN RIB é perfeito para operações de trabalho de terreno e de transporte.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	90 A8

Dimensions US Standard

Usa code	94064618
Ply Rating	8
Section Width (inch)	7.1
Overall Diameter (inch)	30
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-004107
TRA Code	F2

Load capacity (lbs)

mph / psi	62
25	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 19:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..