

## COMMANDER TWIN RIB - Dados técnicos



### Description

COMMANDER TWIN RIB é um pneu com nervura do piso de 4 rasgos e lamelas laterais nos ombros que assegura uma ótima aderência. O perfil mais largo assegura uma ótima distribuição da carga. A Carcaça robusta e o composto de borracha superior garantem um ciclo de vida prolongado. COMMANDER TWIN RIB é perfeito para operações de trabalho de terreno e de transporte.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Trator 2WD

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	TKPH	ECE
5.00 - 15	STANDARD	F2	82 A6	6	4.00 E		145	665	TT	1	
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5.00 F	170	750	TT	0	E11-106R-004091
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	180	761	TT		E11-106R-004107
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	TT		E11-106R-006953
6.50 - 20	STANDARD	F2	101 A6	8	5.00 F	4.00 E ; 5.50 F	190	875	TT	1	E11-106R-004258

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 19:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..